

XP862-DSP SIGNAL PROCESSING MODULE



- Power PC based with full expansion capability
- Application expandable using stackable daughter cards
- Ideal for DSP, communication, network connectivity and high speed video processing
- Linux/Xilinx based signal processing with free software tools

Standard DSP Package includes:

XP862 Processor Board (6U) with:

- 100 Mhz Motorola Power PC
- 512KB Primary Flash & 8MB Secondary Flash
- 128MB SDRAM and 32KB NVSRAM
- 128MB NAND Flash File System
- Dual 10 & 100 Base T Ethernet & Comm Ports
- Linux Pre-installed

DSP Daughter Cards (stackable 3U) with:

- Reconfigurable FPGA Parallel I/O Controller Interface
- Dual Xilinx Spartan-II FPGA's
- 1MB Dual Port Memory-simultaneously accessible
- Multi-channel A/D and D/A converter functionality
- MATLAB/Simulink compatible

Software Development Kit (CD-ROM)

- The software development kit (PPC-LDK) contains three basic types of software tools, the first is for host computer build software, the second for device communications and the third for target (DSP daughter card) software.
- **Host software**
PPC-LDK includes a complete development toolset that allows the software for the embedded board to be built on the host computer. These tools include:
 - GNU gcc compiler
 - GNU binutils
 - uClibc compact C library
 - gdb debugger
 - jffs2 journalling flash filesystem utilities
 - ruby script language
- **Device Communications software**
PPC-LDK includes communications software that allows the host computer to communicate with the target devices via the serial and ethernet ports. These communication programs include:
 - minicom serial terminal
 - tftp server
 - nfs server

- **DSP Target software**

The PPC-LDK target software provides a complete platform for developing embedded linux solutions on the XP862, including all levels of software from bootloader to applications. Source code for all target software is provided under a Free Software license and includes:

- Bootloader
- Hardware diagnostics
- Linux kernel includes drivers for all devices on the XP862 boards including:
 - ethernet
 - serial port
 - NOR flash
 - NAND flash
 - LED bank
 - NVRAM
- Current daughter card drivers for XP862-DSP (FPGA, X2SCSI) include:
 - Xilinx reprogrammable co-processor board
 - PCI controller
 - Cardbus controller
 - SCSI controller
- Linux applications include system software, servers, and development tools.
 - busybox system software
 - telnet server
 - boa embedded webserver
 - iptraf network monitor
 - flash utilities

XtremeDSP- Xilinx Web Pak Development Tools (selected)

Optional Daughter cards:

- Auxiliary PCI, SCSI, PCMCIA/Card Bus Interface
- IEEE1394B Firewire/USB Interface
- 1.0GB SDRAM
- Hard Disk Cache

<u>JRM Consultants</u>
Ph: 805-564-3119 Web: www.jrmconsultants.com E: info@jrmconsultants.com

