

## XP862-DSP SIGNAL PROCESSING MODULE



- Power PC based with full expansion capability
- Application expandable using stackable daughter cards
- Ideal for DSP, communication, network connectivity and high speed video processing
- Linux/Xilinx based signal processing with free software tools

### Standard DSP Package includes:

#### XP862 Processor Board (6U) with:

- 100 Mhz Motorola Power PC
- 512KB Primary Flash & 8MB Secondary Flash
- 128MB SDRAM and 32KB NVSRAM
- 128MB NAND Flash File System
- Dual 10 & 100 Base T Ethernet & Comm Ports
- Linux Pre-installed

#### DSP Daughter Cards (stackable 3U) with:

- Reconfigurable FPGA Parallel I/O Controller Interface
- Dual Xilinx Spartan-II FPGA's
- 1MB Dual Port Memory-simultaneously accessible
- Multi-channel A/D and D/A converter functionality
- MATLAB/Simulink compatible

#### Software Development Kit (CD-ROM)

- The software development kit (PPC-LDK) contains three basic types of software tools, the first is for host computer build software, the second for device communications and the third for target (DSP daughter card) software.
- **Host software**  
PPC-LDK includes a complete development toolset that allows the software for the embedded board to be built on the host computer. These tools include:
  - GNU gcc compiler
  - GNU binutils
  - uClibc compact C library
  - gdb debugger
  - jffs2 journalling flash filesystem utilities
  - ruby script language
- **Device Communications software**  
PPC-LDK includes communications software that allows the host computer to communicate with the target devices via the serial and ethernet ports. These communication programs include:
  - minicom serial terminal
  - tftp server
  - nfs server

- **DSP Target software**

The PPC-LDK target software provides a complete platform for developing embedded linux solutions on the XP862, including all levels of software from bootloader to applications. Source code for all target software is provided under a Free Software license and includes:

- Bootloader
- Hardware diagnostics
- Linux kernel includes drivers for all devices on the XP862 boards including:
  - ethernet
  - serial port
  - NOR flash
  - NAND flash
  - LED bank
  - NVRAM
- Current daughter card drivers for XP862-DSP (FPGA, X2SCSI) include:
  - Xilinx reprogrammable co-processor board
  - PCI controller
  - Cardbus controller
  - SCSI controller
- Linux applications include system software, servers, and development tools.
  - busybox system software
  - telnet server
  - boa embedded webserver
  - iptraf network monitor
  - flash utilities

#### **XtremeDSP- Xilinx Web Pak Development Tools (selected)**

#### **Optional Daughter cards:**

- Auxiliary PCI, SCSI, PCMCIA/Card Bus Interface
- IEEE1394B Firewire/USB Interface
- 1.0GB SDRAM
- Hard Disk Cache

<b><u>JRM Consultants</u></b>
Ph: 805-564-3119 Web: <a href="http://www.jrmconsultants.com">www.jrmconsultants.com</a> E: <a href="mailto:info@jrmconsultants.com">info@jrmconsultants.com</a>

